

Unified Threat Management



Cyberoam CR500i

Comprehensive Network Security for Small and Medium Enterprises

Cyberoam CR500i is an identity-based security appliance that delivers real-time network protection against evolving Internet threats to small and medium enterprises (SMEs) through unique user based policies.

SMEs face same amount of risk as large enterprises from Internet attacks but have limited technical resources to manage security solutions. Cyberoam protection is comprehensive, yet cost-effective and easy-to-manage. CR500i appliances deliver comprehensive protection to SMEs with Stateful Inspection Firewall, VPN, Gateway Anti-Virus and Anti-Spyware, Gateway Anti-Spam, Intrusion Detection and Prevention, Content Filtering, Bandwidth Management, Multiple Link Management, Comprehensive Reporting over a single platform and can be centrally managed using the Cyberoam Central Console. Integrated high availability provides protection against hardware failure to maximize network uptime and ensure uninterrupted access.

Identity-based Security in UTM

Cyberoam attaches the user identity to security, taking enterprises a step ahead of conventional solutions that bind security to IP-addresses. Cyberoam's identity-based security offers full business flexibility while ensuring complete security in any environment, including DHCP and Wi-Fi, by identifying individual users within the network-whether they are victims or attackers.



Instant and complete visibility into patterns of usage
Instant identification of victims and attackers in internal network

Features	Description	Benefits
Stateful Inspection Firewall (ICSA Labs Certified)	 Powerful stateful and deep packet inspection Prevents DoS and flooding attacks from internal and external sources Identity-based access control for applications like P2P, IM 	Application layer protectionFlexibility to set policies by user identityHigh scalability
Virtual Private Network	 Industry standard: IPSec, L2TP, PPTP VPN VPN High Availability for IPSec and L2TP connections Dual VPNC Certifications - Basic and AES Interop 	Secure connectivity to branch offices and remote users Low cost remote connectivity over the Internet Effective failover management with defined connection priorities
Gateway Anti-Virus & Anti-Spyware	 Scans HTTP, FTP, IMAP, POP3 and SMTP traffic Detects and removes viruses, worms and Trojans Access to quarantined mails to key executives Restriction on file transfer based on keywords Instant user identification in case of HTTP threats 	 Complete protection of traffic over all protocols High business flexibility Protection of confidential information Real-time security
Gateway Anti-Spam	Scans SMTP, POP3 and IMAP traffic for spam Detects, tags and quarantines spam mail Lenient and strict policies based on user need Enforces black and white lists Virus Outbreak Protection Content-agnostic spam protection including Image-spam using Recurrent Pattern Detection (RPD™) Technology	 Enhances productivity High business flexibility Protection from emerging threats High scalability Zero hour protection incase of virus outbreaks Multi-language and Multi-format spam detection
Intrusion Detection & Prevention - IDP	 Database of over 3000 signatures Multi-policy capability with policies based on signature, source and destination Internal user identification Detect and prevent intrusion using custom signatures Prevents intrusion attempts, DoS attacks, malicious code, backdoor activity and network-based blended threats Blocks anonymous proxies with HTTP proxy signatures Blocks "phone home" activities 	 Low false positives Real-time Security in dynamic environments like DHCP and Wi-Fi Offers instant user-identification in case of internal threats Apply IDP policies on users
Content & Application Filtering	 Automated web categorization engine blocks non-work sites based on millions of sites in over 68 categories URL Filtering for HTTP & HTTPS protocols Hierarchy, department, group, user-based filtering policies Time-based access to pre-defined sites Prevents downloads of streaming media, gaming, tickers, ads Supports CIPA compliance for schools and libraries 	 Prevents exposure of network to external threats Blocks access to restricted websites Ensures regulatory compliance Saves bandwidth and enhances productivity Protects against legal liability Ensures the safety and security of minors online Enables schools to qualify for E-rate funding
Bandwidth Management	Committed and burstable bandwidth by hierarchy, departments, groups & users	Prevents bandwidth congestionPrioritizes bandwidth for critical applications
Multiple Link Management	Security over multiple ISP links using a single appliance Load balances traffic based on weighted round robin distribution Link Failover automatically shifts traffic from a failed link to a working link	 Easy to manage security over multiple links Controls bandwidth congestion Optimal use of low-cost links Ensures business continuity
On-Appliance Reporting	Complete Reporting Suite available on the Appliance Traffic discourse offers real time reports.	Reduced TCO as no additional purchase required Instant and complete visibility into patterns of upga-

Traffic discovery offers real-time reports

Reporting by username


Interfaces 10/100 Ethernet Ports 10/100/1000 GBE Ports Configurable Internal/DMZ/WAN Ports Console Ports (RJ45) SFP (Mini GBIC) Ports USB ports	- 6 Yes 1 - 2	User Identity and Group Based Controls Access time restriction Time Quota restriction Schedule based Committed and Burstable Bandwidth Data Quota restriction Schedule based P2P and IM Controls
System Performance Concurrent sessions New sessions/second Firewall throughput (Mbps) 168-bit Triple-DES/AES throughput (Mbps) Antivirus throughput (Mbps) IDP throughput (Mbps) UTM throughput (Mbps)	400,000 20,000 2Gbps 200/250 450 500 320	Networking Multiple Link Auto Failover WRR based Load balancing Policy routing based on Application and User DDNS/PPPOE Client Support for TCP MSS configuration Support for HTTP Proxy Mode Deployment Parent proxy support Dynamic Routing: RIP v1& v2, OSPF, BGP Multicast Forwarding
Stateful Inspection Firewall Multiple Zones security with separate levels of access rule enforcement for each zone Rules based on the combination of User, Source & Destination Zone and IP address and Service	Yes Yes	High Availability Active-Passive with state synchronization Stateful Failover Alert on Appliance Status change
Actions include policy based control for IDP, Content Filtering, Anti virus, Anti spam and Bandwidth Management Access Scheduling Policy based Source & Destination NAT H.323 NAT Traversal 802.1q VLAN Support	Yes Yes Yes Yes Yes	Administration Web-based configuration wizard Role-based administration Multiple administrators and user levels Upgrades & changes via Web UI
DoS Attack prevention Gateway Anti-Virus & Anti-Spyware Virus, Worm, Trojan Detection & Removal Spyware, Malware, Phishing protection Automatic virus signature database update	Yes	System Management Web UI (HTTPS) Command line interface (Serial, SSH, Telnet) SNMP (v1, v2c, v3) Cyberoam Central Console
Scans HTTP, FTP, SMTP, POP3, IMAP Customize individual user scanning Self Service Quarantine area Scan and deliver by file size Block by file types Add disclaimer/signature		User Authentication Local database Windows Domain Control & Active Directory Integration Automatic Windows Single Sign On External LDAP/RADIUS database Integration
Gateway Anti-Spam Real-time Blacklist (RBL), MIME header check Filter based on message header, size, sender, recipient Subject line tagging IP address blacklist/exempt list	Yes Yes Yes Yes	Logging/Monitoring Internal HDD Graphical real-time and historical monitoring Email notification of reports, viruses and attacks Syslog support On-Appliance Reporting Intrusion events reports Policy violations reports Web Category reports (user, content type) Search Engine Keywords reporting Data transfer reporting (By Host, Group & IP Address) Virus reporting by User and IP Address Compliance Reports VPN Client IPSec compliant Inter-operability with major IPSec VPN Gateways Supported platforms: Windows 98, Me, NT4, 2000, XP, Vista Import Connection configuration
Redirect spam mails to dedicated email address Image-based spam filtering using RPD Technology Zero hour Virus Outbreak Protection Self Service Quarantine area	Yes	
Dynamic Intrusion Detection & Prevention Signatures: Default (3000+), Custom IDP Policies: Multiple, Custom User-based policy creation		
Automatic real-time updates from CRProtect networks Protocol Anomaly Detection P2P applications signatures including Skype Content & Application Filtering		
Inbuilt Web Category Database URL, keyword, File type block Categories: Default(68+), Custom HTTP Upload block Protocols supported: HTTP, HTTPS	Yes Yes Yes Yes Yes	Certification ICSA Firewall - Corporate VPNC - Basic and AES interoperability Checkmark UTM Level 5 Certification
Block Malware, Phishing, Pharming URLs Custom block messages per category Block Java Applets, Cookies, Active X CIPA Compliant	Yes Yes Yes Yes	Compliance CE FCC
Virtual Private Network - VPN IPSec, L2TP, PPTP Encryption - 3DES, DES, AES, Twofish, Blowfish, Serpent Hash Algorithms - MD5, SHA-1 Authentication - Preshared key, Digital certificates	Yes Yes Yes Yes	Dimensions H x W x D (inches) H x W x D (cms) Weight
IPSec NAT Traversal Dead peer detection and PFS support Diffie Hellman Groups - 1,2,5,14,15,16 External Certificate Authority support Export Road Warrior connection configuration	Yes Yes Yes Yes Yes	Power Input Voltage Consumption Total Heat Dissipation (BTU)
Domain name support for tunnel end points VPN connection redundancy Bandwidth Management	Yes Yes	Environmental Operating Temperature Storage Temperature
Application and User Identity based Bandwidth Management Guaranteed & Burstable bandwidth policy Application & User Identity based Traffic Discovery Multi WAN bandwidth reporting	Yes Yes Yes Yes	Relative Humidity (Non condensing) Cooling System - Fans











India - Sales: +91-79-66065606 | Support Toll Free: 1-800-301-00013

EMEA/APAC - Sales: +91-79-66065787 | Support: +91-79-66065777

Copyright © 1999 - 2008 Elitecore Technologies Ltd. All rights reserved.

Cyberoam and Cyberoam logo are registered trademark of Elitecore Technologies Ltd. Although Elitecore has attempted to provide accurate information

Elitecore assumes no responsibility for accuracy or completeness of information neither is this a legally binding representation. Elitecore has the right to



Yes Yes Yes Yes Yes

Yes Yes Yes Yes Yes Yes Yes Yes

Yes Yes Yes

Yes Yes Yes Yes

Yes Yes Yes Yes

Yes Yes Yes Yes

Yes Yes Yes Yes

Yes Yes Yes Yes Yes Yes 45+

Yes Yes Yes

Yes

Yes Yes Yes

Yes Yes

1.72 x 16.8 x 13.4 4.4 x 42.7 x 34.0 6.7 kg, 14.77 lbs

110-240 VAC 82W 280

0 to 40 °C -20 to 80 °C 10 to 90%

